W9691

1" Ext. anvil" Cordless Impact Wrench, 3000 Nm (2200 lb-ft)



The Ingersoll Rand 1in cordless impact wrench combines the power of air with the freedom of cordless mobility. Give your operators the ability to move freely, in applications where space and maneubrability are at a premium. W9691 immediatly gives the oper

- 4000 Nm (3000 ft-lb) of Nut Busting Torque - that's the best-in-class performance.
- All-metal impact mechanism and drive train provide the ultimate in durability and reliability.
- High-durability brushless motor
- Engineered composite housing for increased protection against chemical attack.
- Over-molded soft-touch grip minimizes vibration, reduces fatigue and enhances user comfort.
- Variable speed switch with electronic brake provides maximum control of the tool.
- IQV Power Control System includes 4 modes: Full Power Reverse, Shut off 250 Nm, Snug up 550 Nm, and Full Power Forward
- High-capacity 5.0 Ah battery delivers maximum performance and runtime.
- Tool only is delivered without battery and charger.
  Kit K4E contains: cordless tool, 4 pcs 20 V, 5.0 Ah Li-ion batteries and Dual Bay charger

Specifications

Part Number	**W9691**
Ordering number (tool only)	**W9691**
Part Number (kit)	**W9691-K4E-EU**
Ordering number (kit)	**W9691-K4E-EU**
Voltage (DC)	**40 (2x20) V**
Drive size (square)	**1" Ext. anvil in**
Other available versions:	
- 1" square drive	**W9491**

PERFORMANCE

Maximum torque in forward	**2200 ft-lb / 3000 Nm**
Maximum torque in reverse	**2200 ft-lb / 3000 Nm**
Nut busting torque	**3000 ft-lb / 4000 Nm**
Free speed	**0 - 890 rpm**
Free speed (Shut off mode 1)	**0 - 500 rpm**
Free speed (Shut off mode 2)	**0 - 550 rpm**
Impacts per minute	**1170**

NOISE & VIBRATION

Sound pressure / power (EN62841)	**95.9 / 106.9 dB(A)**
Vibration level / measurement uncertainty (EN62841)	**23.5 / 7.7 m/s²**

WEIGHT & DIMENSIONS

Tool weight with battery	**29.1 lb / 13.2 kg**
Tool dimensions with battery (L x W x H)	**663 x 176 x 206 mm**
Shipping weight (tool only)	**25.9 lb / 11.7 kg**
Shipping weight (kit 5.0Ah)	**39.9 lb / 18.1 kg**
Shipping dimensions (tool only) (L x W x H)	**750 x 264 x 254 mm**
Shipping dimensions (kit) (L x W x H)	**750 x 264 x 254 mm**
UPC / EAN code (tool only)	**6 63023 15572 2**
UPC / EAN code (Kit 5.0 Ah)	**6 63023 15579 1**
Origin	**Tool and charger from PRC. Batteries from TW**

CE

© 2021 Ingersoll-Rand Company — Form No. PDS_W9691_EN_1/2_24/06/2021

W9691
ACCESSORIES



SK8M4LN
SK8M4LN
1" Impact socket set (4 pcs) (27, 30, 32 and 33 mm)



TL-W9691-600
TL-W9691-600
Hanger kit



BL2022
47515902001
Li-Ion battery, 20 V, 5.0 Ah



BC1221-EU
BC1221-EU
Dual Bay charger 12/20V



170-1 LB
04650073
Grease for impct mechanism (high temperature) 0.45 kg



TB3
80233786
Tool Bag



BL2010-BOOT
47510964001
Protective battery boot BL2010/ BL2022



BC1121-EU
47507874001
Universal battery charger 12/20V

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.

© 2021 Ingersoll-Rand Company — Form No. PDS_W9691_EN_2/2_24/06/2021